



400 series Built-In Fully Automatic Coffee Machine, Stainless steel behind glass

CM450111

- Handleless door / automatic door opening
- Continuous flow heater means no waiting time and constant brewing temperature
- Aroma brewing technology for a full aroma
- Single portion cleaning
- TFT touch display
- Panel-free appliance with surface control module
- One-touch operation
- Personalisation function
- 7 light settings
- Electronic fill level control for milk, water and coffee to ensure a perfect result

Type of beverage

- Ristretto / 2 x Ristretto. Espresso / 2 x Espresso. Espresso Macchiato / 2 x Espresso Macchiato. Coffee / 2 x Coffee. Americano / 2 x Americano. Caffè Latte / 2 x Caffè Latte. Latte Macchiato / 2 x Latte Macchiato. Cappuccino / 2 x Cappuccino. Flat White / 2 x Flat White. Milk froth / 2 x

Milk froth. Warm milk / 2 x Warm milk. Hot water / 2 x Hot water.

Handling

- Automatic door opening.
- Rotary knob and TFT touch display operation.
- Clear text display.
- Personalisation function, option to save 8 individualised beverages.
- 4 beverage size settings, volume can be individually adjusted to match the size of the cup.
- 8 coffee strength levels from very mild to extra strong.
- 3 coffee temperature levels.
- 10 hot water temperature levels.
- 4 coffee-milk ratio levels.
- Adjustable grinding level.
- Height-adjustable coffee dispenser 7 cm to 15 cm.
- Easy access to water tank, milk and coffee bean container behind the door.

Features

- Maintenance-free grinding unit with ceramic discs.
- Separate drawer for second ground coffee type.
- Water pump with 19 bar pressure.
- Double grinding and brewing cycles for extra intensity for single beverage order.

- For double beverage order, two grinding and brewing cycles.
- Beverage dispenser with integrated milk system.
- Insulated stainless steel milk container for up to 0.5 litres.
- Integrated lightning with LEDs.
- Removable bean container with aroma protecting lid for 500 g allows for an effortless exchange of different types of coffee beans.
- Automatic adjustment of ground coffee quantity.
- Removable 2.4 litre water tank.
- Electronic water filter exchange indicator.
- Electronic fill level control for drip tray and container for coffee residue.

Safety

- Child lock.

Cleaning

- Fully automatic rinse programme when machine is turned on/off.
- Automatic steam cleaning of the milk system after every beverage.
- Automatic cleaning and descaling programme.
- Emptying programme to prepare the appliance for holiday or transportation.

The difference is GAGGENAU



- Empty-grinding function to remove coffee residues from the system when switching bean types.
- Removable brewing unit.
- Dishwasher-safe coffee residue container and drip tray.
- Dishwasher-safe beverage dispenser.

Planning notes

- Ideal installation height 95 cm to 145 cm (top edge of niche bottom).
- The door panel surface of the appliance extends 47 mm from the furniture cavity.
- When installing in a corner a side clearance is required.
- Door opening angle appr. 110° (delivery status) - mounting distance to the wall has to be at least 350 mm.
- Door opening angle appr. 155° - mounting distance to the wall has to be at least 650 mm.
- Door opening angle appr. 92° - mounting distance to the wall has to be at least 100 mm (spare part No. 00636455).
- Installation directly above 14 cm high warming drawer in 59 cm standardised niche.
- Special accessories (order as spare parts): Part No. 17000705 Water filter
Part No. 00311819 Descaling tablets
Part No. 00311769 Cleaning tablets Part No. 00636455 Door hinge restrictor (92°

opening angle) Part No. 11015223 Bean container with lid

Connection

- Total connected load 1.6 KW.
- Connection cable 1.7 m, pluggable.