



400 series Built-in compact oven with steam function, Door Hinge: right

BS470102

- Handleless door / automatic door opening
- Fixed inlet and outlet water connection
- Cleaning system, fully automatic
- Large cavity
- 2 LED light sources
- External steam generation
- Steaming without pressure
- Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%
- Sous-vide cooking with accurate temperature regulation
- Full surface grill behind glass ceramic, combinable with circulated air up to 230 °C and steam
- Automatic programmes
- Core temperature probe with estimation of cooking time
- Hot air fan rotates in both directions for ideal heat distribution
- TFT touch display
- Panel-free appliance with surface control module

- Electronic temperature control from 30 °C bis 230 °C
- Net volume 50 litres

Heating methods

- Hot air + 100 % humidity. Hot air + 80 % humidity. Hot air + 60 % humidity. Hot air + 30 % humidity. Hot air + 0 % humidity. Low temperature cooking. Sous-vide cooking. Full surface grill level 1 + humidity. Full surface grill level 2 + humidity. Full surface grill + circulated air. Dough proofing. Defrosting. Regenerating.

Handling

- Automatic door opening.
- Rotary knob and TFT touch display operation.
- Clear text display.
- Option to save individual recipes (incl. core temperature probe).
- Personalisation of automatic programmes.
- Information key with use indicators.
- Side-opening door opens up to 180° angle.

Features

- Full surface grill 2 KW behind glass ceramic.
- Steam removal.
- Misting.

- Three-point core temperature probe with automatic shut-off and estimation of cooking time.
- Automatic programmes.
- Actual temperature display.
- Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
- Automatic boiling point detection.
- Capacity display for filter cartridge (if connected to GF 111 100 descaling system).
- 2 x LED light on the side.
- Hygienic stainless steel cooking interior.
- 3 tray levels.
- Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.
- The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Safety

- Child lock.
- Safety shut-off.
- Cooled housing with temperature protection.

The difference is GAGGENAU



Cleaning

- Cleaning programme, fully automatic.
- Descaling programme for the steam generator.
- Drying programme.
- Automatic drying of the cavity at the end of the cooking process.
- Strainer filter, removable.
- Demo cleaning programme.

Planning notes

- Door hinge not reversible.
- No other electrical appliances should be installed above the BS.
- At no point may the outlet hose be positioned higher than the bottom edge of the appliance. The outlet hose must also be at least 100 mm lower than the appliance outlet (see drawing "drainage connection").
- Inlet hose can be extended once.
- The outlet hose must not be longer than a maximum of 5 m.
- The water connection (1) for the inlet hose must always be accessible and not located directly behind the appliance.
- The connection of the outlet hose to the siphon (2) must not be directly behind the appliance and should be accessible.
- The descaling system GF 111 100 (3) must be installed when connecting the

appliance if the water hardness exceeds 7° dH.

- The facade of the appliance extends 47 mm from the furniture cavity.
- Consider the overhang when planning to open drawers next to the appliance.
- When planning a corner solution, pay attention to the 90° door opening angle.
- The mains socket needs to be planned outside the built-in niche.
- Special accessories (order as spare part): Part No. 17002490 Descaling tablets.

Connection

- Energy efficiency class A at a range of energy efficiency classes from A+++ to D.
- Total connected load 3.1 KW.
- Only cold water connection.
- Inlet hose 3.0 m with 3/4 " (26,4 mm) connection, extendable.
- Outlet hose (ø 24 mm) 3.0 m (HT-Hose).
- Connecting cable 1.8 m with plug.
- Plan a LAN cable.
- Power consumption standby/display on 0.8 W.
- Power consumption standby/display off 0.5 W.
- Power consumption standby/network 1.8 W.
- Time auto-standby/display on 20 min.
- Time auto-standby/display off 20 min.
- Time auto-standby/network 20 min.

- Please check the user manual for how to switch off the WiFi module.